

বাংলাদেশ স্ট্যান্ডার্ডস এন্ড টেস্টিং ইন্সটিটিউশন

শিল্প মন্ত্রণালয়

গণপ্রজাতন্ত্রী বাংলাদেশ সরকার

মান ভবন, ১১৬/ক, তেজগাঁও শিল্প এলাকা, ঢাকা-১২০৮।

ফোন: ৮৮৭০২৭৫, ৮৮৭০২৭৭, ৮৮৭০২৭৮, ৮৮৭০২৭৯, ৮৮৭০২৮০, ৮৮৭০২৮১, ৯১৩১৫৮২

Fax: 88-02-9131581, E-mail: dg@bsti.gov.bd, bsti@bangla.net,, Website: www.bsti.gov.bd

স্মারক নং ৩৬.০৫.০০০০.০০২.১২.৫০৩.১৯/১৭(৪)

তারিখ:

১০ ফাল্পুন ১৪২৭ বজ্গাব্দ

২৩ ফেব্রুয়ারি ২০২১ খ্রিষ্টাব্দ

বিষয়: টেকনিক্যাল কমিটি কর্তৃক প্রাথমিকভাবে অনুমোদিত খসড়া মান-এর উপর মতামত আহ্বান প্রসঙ্গে।

উপর্যুক্ত বিষয়ে আদিষ্ট হয়ে জানানো যাচেছ যে, জাতীয় মান প্রণয়ন/রিভিশন/অ্যামেভমেন্ট-এর নিমিত্ত বিএসটিআই গঠিত 'মিল্ক এভ মিল্ক প্রোডাক্টস' টেকনিক্যাল কমিটি কর্তৃক নিম্প্রবর্ণিত দুটি বাংলাদেশ জাতীয় মান রিভিশনের লক্ষ্যে প্রাথমিকভাবে অনুমোদিত হয়:

- i) BDS 1805 UHT Treated Milk (Draft for 1st Rev.)
- ii) BDS 1866 Pasteurized low fat milk and standardized milk (Draft for 1st Rev.)
- ২। টেকনিক্যাল কমিটি কর্তৃক প্রাথমিকভাবে অনুমোদিত খসড়া মান দুটি নিয়মানুযায়ী কৃষি ও খাদ্য বিভাগীয় কমিটি কর্তৃক চূড়ান্ডভাবে অনুমোদনের পূর্বে আপনার/আপনার প্রতিষ্ঠানের মতামত আহ্বান করা যাচেছ। বিবেচ্য মানটির উপর কোনরূপ মতামত যদি থাকে, তবে তা যৌক্তিকতা উল্লেখপূর্বক প্রদানের নিমিত্ত মান দুটির খসড়া এতদ্সঙ্গে প্রেরণ করা হলো।
- ৩। এমতাবছায়, রিভিশনের লক্ষ্যে প্রস্তাবিত খসড়া মান দুটির উপর যৌক্তিক কোন মতামত (যদি থাকে), তবে তা আগামী ২২ এপ্রিল ২০২১ খ্রিঃ তারিখের মধ্যে নিমুম্বাক্ষরকারী বরাবর প্রেরণের জন্য অনুরোধ করা হলো। নির্ধারিত সময়ের মধ্যে কোনরূপ মতামত না পাওয়া গেলে প্রস্তাবিত খসড়া মানটির সাথে আপনি/আপনার প্রতিষ্ঠান সম্মত রয়েছেন বিবেচনান্তে পরবর্তী কার্যক্রম গ্রহণ করা হবে।
- ৪। জাতীয় মান প্রণয়নে সকলের সহযোগিতা একান্তভাবে কাম্য।

(গোলাম মোঃ সরওয়ার)

উপপরিচালক (কৃষি ও খাদ্য)

মোবাঃ ০১৭১৮৪৬৩৬৬২

ইমেইল: sarwarbsti99@gmail.com

সংযুক্তি: বর্ণনামতে।

বিতরণ প্রয়োজনীয় কার্যার্থে (জেষ্ঠ্যতার ক্রমানুসারে নয়):

- ১। সংশ্লিষ্ট সকল স্টেকহোল্ডার ও কমিটির সদস্যবৃন্দ।
- ২। চেয়ারম্যান, বাংলাদেশ নিরাপদ খাদ্য কর্তৃপক্ষ, প্রবাসী কল্যাণ ভবন, ৭১-৭২ ইন্ধাটন গার্ডেন রোড, ঢাকা।
- ৩। মহাপরিচালক, জাতীয় ভোক্তা অধিকার সংরক্ষণ অধিদপ্তর, টিসিবি ভবন, ১ কাওরান বাজার, ঢাকা।
- ৪। সভাপতি, এফবিসিসিআই, ৬০ মতিঝিল বাণিজ্যিক এলাকা, ঢাকা-১০০০।
- ৫। সভাপতি, এমসিসিআই, ১২২-১২৪ মতিঝিল বাণিজ্যিক এলাকা, ঢাকা-১০০০।
- ৬। সভাপতি, ক্নজ্যুমার্স এসোসিয়েশন অব বাংলাদেশ (ক্যাব), ৮/৬ সেগুনবাগিচা, ঢাকা-১০০০।
- ৭। পরিচালক (সিএম), বিএসটিআই, ঢাকা।
- ৮। প্রিচালক (রসায়ন), বিএসটিআই, ঢাকা।

😿 পরিচালক (প্রশাসন), বিএসটিআই, ঢাকা। [দৃঃ আঃ প্রোগ্রামার, আইসিটি সেল, ওয়েবসাইটে দেয়ার জন্য]

CANTUNO!

29/12

Bangladesh Standard SPECIFICATION FOR ULTRA HIGH TEMPERATURE (UHT) TREATED MILK (Draft for First Revision)

1. SCOPE

1.1 This standard prescribes the requirements and the method of sampling and tests for Ultra High Temperature (UHT) treated milk.

REFERENCES

2.1 The Bangladesh Standards listed in Annex A is necessary adjuncts to this standard. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

3. TERMINOLOGY

- 3.1 For the purpose of the specification the following definitions shall apply:
- **3.2 Milk**—Milk is the normal lacteal secretion derived from complete milking of healthy animal without either addition of thereto or extraction therefrom. It shall be free from colostrum and obtained by the complete milking of one or more healthy animals (cow, buffalo, sheep or goat).
- **3.3** Whole milk/Full cream milk Whole milk/Full cream milk means any of the milk mentioned under section **3.2** or adding water¹ in Whole milk powder/Full cream milk powder which obtain through spray-drying process (comply with the requirements of BDS 860). In both cases, minimum milk fat and milk solids-not-fat content are 3.5 and 8.0 respectively.
- 3.4 Whole milk powder/Full cream milk powder A product obtained by the removal of water only from milk of cow, buffalo, sheep or goat (see section 3.3) through spray-drying process and comply with the requirements of BDS 860.
- 3.5 Skimmed milk powder A product obtained by the removal of water only from skimmed milk (see section 3.11) of cow, buffalo, sheep or goat (section 3.2) through spray-drying process and comply with the requirements of BDS 860.
- 3.6 Standardized milk Milk prepared by adjusting fat and/or solids—not-fat (SNF) content to a certain pre-determined level. The standardization can be done by partially skimming of fat in the milk with a cream separator, or by admixture with fresh or reconstituted skimmed milk/reconstituted whole milk in proper proportions to adjust prescribed milk fat and SNF content.
- **3.7** Reconstituted milk Milk prepared by dispersing whole milk powder/full cream milk powder (see section **3.4**) in water in the amount necessary to re-establish the appropriate water-to-solids ratio to achieve similar characteristics and appropriate compositional requirements of whole milk.
- 3.8 Toned milk Milk obtained by addingwater¹ and skimmed milk powder (see section 3.5) to whole milk.

¹Water means drinking water, which obtain from a treatment process and conform BDS 1240

- **3.9 Medium fat milk Medium fat milk which obtain from milk (see section 3.2) having milk fat minimum 2.0 % (m/m) and not more than 3.4 % (m/m).**
- 3.10 Low fat milk Low fat milk which obtain from milk (see section 3.2) having milk fat minimum 0.5 % (m/m) and not more than 1.9 % (m/m).
- 3.11 Fat free or skimmed milk Fat free or skimmed milk which obtain from milk (see section 3.2) having milk fat less than 0.5 % (m/m).
- 3.12 UHT treated milk Milk, described in section 3.2 to 3.11 has undergone through processes mentioned in section 4 and fulfilled the requirements described insection5 of this standard.
- 3.13 UHT whole/full cream milk Whole/full cream milk mentioned in section 3.3 that has undergone through processes mentioned in section 4 and fulfilled the requirements described in section5 of this standard.
- **3.14 UHT standardized milk** Standardized milk mentioned in section **3.6** that has undergone through processes mentioned in section **4** and fulfilled the requirements described in **5** of this standard.
- 3.15 UHT reconstituted milk Reconstituted milk mentioned in section 3.7 that has undergone through processes mentioned in section 4 and fulfilled the requirements described insection5 of this standard.
- **3.16 UHT toned milk –** Toned milk mentioned in section **3.8** that has undergone through process mentioned in section 4 and fulfilled the requirements described in section 5 of this standard.
- **3.17 UHT medium fat milk Medium** fat milk mentioned in section **3.9** that has undergone through processes mentioned in section **4** and fulfilled the requirements described in section **5** of this standard.
- 3.18 UHT low fat milk Low fat milk mentioned in section 3.10 that has undergone through processes mentioned in section 4 and fulfilled the requirements described in section 5 of this standard.
- 3.19 UHT fat free or skimmed milk Fat free or skimmed milk mentioned in section 3.11 that has undergone through processes mentioned in section 4 and fulfilled the requirements described in section 5 of this standard.

4 Ultra High Temperature (UHT) Method

- a) Milk (see section 3.2 to 3.11) treated by the direct culinary steam injection method, water¹may be introduced into the milk (see section 3.2 to 3.11) by direct culinary steam injection, provided that this process is necessary for manufacture and that exactly the same amount of water¹vapour is driven off as was introduced into the milk. Water shall not be otherwise introduced to the milk.
- b) Milk (see section 3.2 to 3.11) treated by the ultra-high temperature method shall efficiently heated to and maintained at not less than 135 °C for not less than 2 seconds then followed by immediate cooling and aseptic packaging into sterile hermetically sealed containers in which it is supplied to the consumer and kept in a wholesome state at room temperature for not less than fifteen days from the date of manufacture.
- c) All UHT treated milk (see section 3.13 to 3.19) should be homogenized. There should be no visible separation of fat after 48 hours of quiescent storage at 7 °C. The fat percentage of the top 100 ml of milk in a one liter bottle or of proportionate volumes in containers or other sizes, does not differ by more than 10% from the fat percentage of the remaining milk as determined after thorough mixing (see Annex B).

¹Water means drinking water, which obtain from a treatment process and conform BDS 1240

5. REQUIREMENTS

Physical, chemical and microbiological requirements of UHT treated milk are as follows:

- **5.1 Description** All UHT treated milk (see section **3.13** to **3.19**) shall have white yellowish opaque colour with fresh sweetish characteristic flavour of milk. It shall be free from visible dirt and extraneous matter. UHT treated milk shall not contain whey powder, preservatives, detergent or any other added substances except water¹ (only for reconstituted milk).
- **5.1.1** All products shall be free from any kind of foreign fat (other than milk fat) and solids. Milk fat in any form like cream, butter, butter oil, ghee, etc. are not allowed to add in any UHT treated milk for standardization and reconstitution purpose.
- **5.2 Hygienic condition –** The products shall be prepared in the premises maintained in accordance with BDS 822.

5.3 Legal Requirement

The products shall also comply in all other aspects with the requirements of the legislations enforced in the country.

5.4 The products shall also comply with the requirements given in Table 1

TABLE 1: REQUIREMENT FOR UHT TREATED MILK

SI No.	Characteristic	Requirement	Method of Test
(1)	(2)	(3)	(4)
i)	Fat, percent by mass,		AOAC 905.2/ISO 2446
	a) UHT whole milk	a) Min. 3.5	
	b) UHT standardized milk	b) Min. 3.5	
	c) UHT reconstituted milk	c) Min. 3.5	
	d) UHT toned milk	d) Min. 2.0	
	e) UHT medium fat milk	e) 2.0 - <3.5	
	f) UHT low fat milk	f) 0.5 - <2.0	
	g) UHT fat free or skimmed milk	g) Max. 0.5	
ii)	Solids Non Fat (SNF), percent by mass, Min.	8.0	ISO 6731
		9.0*	
iii)	Density, g/ml at 15.5 °C	1.028 - 1.036	See note-1
iv)	Lactose, percent by mass, Min.	4.4	ISO 5548
v)	Protein, percent by mass, Min.	3.0	ISO 8968-1
vi)	Titratable acidity (as Lactic acid per 100 ml of milk), Max.	0.18	ISO TS 22113:2012
vii)	Total plate count, CFU/ml, Max.	10	ISO 4833-1
viii)	Coliform count, CFU/mI	absent	Annex C
ix)	Alcohol test	Negative	Annex E

^{*} Solids-not-fat (SNF), percent by mass, Min. subject to UHT toned milk only

NOTE 1: Density of normal milk may be determined by hydrometer (lacto-meter)

¹Water means drinking water, which obtain from a treatment process and conform BDS 1240

- 5.5 Pesticides and veterinary drug residues, heavy metal and Aflatoxin M₁
- **5.5.1** The product may comply with the requirements described in Bangladesh Food Safety Authority Regulation. This characteristic shall be tested only if considered as necessary.

6. Packing and Marking

- **6.1** Packing The UHT treated milk (see section 3.12 to 3.19) shall be filled in clean, sound and sanitary containers made of glass or food grade polyethylene pouches, inner laminated tetra pack, plastic containers, cans or any other suitable materials or dispensing units. The product when marketed shall be packaged in well-sealed containers in order to prevent spoilage or contamination of the product. The packaging material used shall be food grade light proof, gas proof, mechanically strong, non-toxic and do not impart any off-flavour to the milk.
- **6.1.1** All packets/containers shall be clean and free from chips, cracks and any other defects. Bottles shall be hermetically sealed with new and clean closures and cans shall be sealed with new and clean can closures. The plastic container shall be heat sealed along one or more edges and shall not leak after it is filled with the products. All containers shall be subjected to cleansing and sanitizing process before filling.
- **6.2 Labeling** All labelling information shall be in Bangla and if necessary, any other suitable languages. The following information shall appear legibly on each container or label. Labels shall be clear in readable form of normal vision, easily visible and pasted securely. Brand name and product name shall be close together front panel preferably in similar font size. Product name shall not smaller than two font size of the brand name.
 - a) Name of the product: 'UHT whole milk/UHT standardized milk/UHT reconstituted milk/UHT toned milk/UHT medium fat milk/UHT low fat milk/UHT fat free or skimmed milk' as applicable;
 - (i) For UHT whole milk/UHT medium fat milk/UHT low fat milk/UHT fat free or skimmed milk declaration on the label shall be "Prepared from fresh whole milk".
 - (ii) For UHT standardized milk/UHT toned milk declaration on the label shall be "Prepared by adding skimmed milk with fresh whole milk"/"Reconstituted skimmed milk with fresh whole milk"/ "Reconstituted milk with fresh whole milk".
 - (iii) For UHT reconstituted milk declaration on the label shall be "Prepared by mixing water with whole milk powder".
 - b) Fat ----- percent [see item (i) of Table 1];
 - c) Batch or code number;
 - d) Name and address of the manufacturer/importer;
 - e) Net volume of the contents in litres or milliliters;
 - f) Nutritional information;
 - f) Date of packing;
 - g) Date of expiry;
 - h) Storage and user instruction;
 - i) Maximum Retail Price (MRP) and
 - j) Any other requirements as specified in the current Legislations and Regulation enforced in the country.
- 6.2.1 The container or label shall be marked with the BSTI Certification Mark
- NOTE 3: The use or BSTI Certification Mark is governed by the provisions of the Bangladesh Standards and Testing Institution Act, 2018 and the Rules and Regulations made there under. Details of conditions under which a licence for the use of BSTI Certification Mark may be granted to manufacturers or processors or importer may be obtained from the Bangladesh Standards and Testing Institution.

7. SAMPLING

7.1 The method of drawing representative samples of the material and the criteria for conformity shall be as prescribed in BDS 1009.

8. TESTS

- 8.1 Tests shall be carried out as prescribed by the methods specified in section 4 (c) and column 4 of Table 1.
- 8.2 Quality of regents Unless specified otherwise, pure chemicals shall be employed in tests and distilled water (see BDS 833) shall be used where the use of water as a reagent is intended.

NOTE4: `Pure chemicals' shall mean chemicals that do not contain impurities, which affect the result of analysis.

Annex A (Clause 2) List of Relevant Standards

BDS and ISO No.	Title
BDS 103	Methods of rounding off numerical value
BDS 822	Code of hygienic conditions for food processing units
BDS 833	Water for laboratory use
BDS 1009	Method of sampling and test for milk and milk products
BDS 1240	Drinking water
ISO 2446:2008	Milk – Determination of milk fat content
ISO 4833-1:2013	Microbiology of the food chain — Horizontal method for the enumeration of microorganisms — Part 1: Colony count at 30 degrees C by the pour plate technique
ISO 5548:2004	Caseins and caseinates - Determination of lactose content - Photometric method
ISO 6731:2010	Milk, cream and evaporated milk – Determination of total solids content (Reference method)
ISO 8968-1	Milk and milk products - Determination of nitrogen content - Part 1: Kjeldahl principle and crude protein calculation
ISO TS 22113:2012	Milk and milk products — Determination of the titratable acidity of milk fat

ANNEX B [Clause 4(C)] Homogenization Test

- B-1 APPARATUS
- B-1.1 Bottle/container, 1 litre (or containers of other sizes)
- B-2 PROCEDURE
- B-2.1 Transfer the milk (1 litre or proportionate volumes) to a one litre bottle or container of other sizes.

- B-2.2 Mix the sample thoroughly.
- **B-2.3** Withdraw 100 ml (or of proportionate volume in containers of other sizes) of the top milk. Determine the fat contain of this milk according to the method as described in ISO 2446 in Table 1.
- B-2.4 Determine also the fat content of the remaining milk
- **B-2.5** Compare the fat content between these two samples. The fat percentage of the top 100 ml of milk in one litre bottle/container (or of proportionate volumes in containers of other sizes) should not differ by more than 10% from the fat percentage of the remaining milk.

ANNEX C [Table 1, item (viii)] DETERMINATION OF COLIFORM COUNT

C-1 GENERAL

C-1.1 Coli form Bacteria – Coliform bacteria include all aerobic and facultative anaerobic gram negative non-spore forming bacteria which ferment lactose with the production of acid and gas. A positive presumptive test is indicated by formation of acid and gas within 48 hours at 35 °C to 37 °C in a fermentation tube containing lactose bile salt broth. Alternatively, the development of dark red colonies at least 0.5 mm in diameter in a solid medium (violet red bile agar) within 20 to 24 hours at 35 °C to 37 °C may be considered as a positive evidence of the presence of coliform bacteria. Violet red bile agar is one of the standard media used for determination of general types of coliform organisms including those of faecal origin in water, milk and other materials or sanitary importance.

C-2 APPARTUS

- C-2.1 Weighing scoop sterile with counter mass (weight)
- C-2.2 Bacteriological transfer pipettes sterile accurately graduated, with cotton plug in the upper orifice.
- C-2.3 Dilution bottles, sterile made of heat-resistance glass (preferably silicate glass) closed with rubber stoppers (preferably screw cap) with new friction-fit liners for making them leak-proff and of the following capacities:
 - a) 150 ml with mark at 99 ml level; and
 - b) 25 ml with mark at 9 ml level.
- C-2.4 Petri dishes with outside dish diameter 100 mm, inside dish diameter 91 mm and depth 15 mm. The exterior and interior surfaces of the bottom should be flat and free from bubbles scratches or other defects which would interfere with counting of colonies.
- C-2.5 Bacteriological tubes sterile 25 ml capacity with a mark at the 10 ml level, with cotton plugs.
- C-2.6 Tubes having inverted vials Durham tubes.

C-3 REAGENT

C-3.1 Dilution water - Dissolve 34 g of potassium dihydrogen phoshate (KH₂PO₄) in 500 ml of distilled water, adjust with 1 N sodium hydroxide solution and make up to one litre with distilled water. Dilute 1.25 ml of this stock phoshpate buffer solution with distilled water to one litre to obtain dilution water.

C-3.2 Medium - Violet red bile agar of following composition and pH shall be used as the medium:

Yeast extract	3.0 g
Peptone	7.0 g
Sodium taurocholate	1.5 g
Lactose	10.0 g
Sodium chloride	5.0 g
Agar-agar	20.0 g
Indicator	
Neutral red	0.03 g
Crystal violet	0.002 g
Water	100 ml
Final pH	7.4 ± 0.1

C-3.2.1 Preparation and sterilization of medium - Soak the materials (C-3.20) for 3 to 5 minutes in cold water, then bring the mixture into complete solution with minimum delay by boiling above asbestos centered wire gauze, over a flame. Stir continuously and efficiently to avoid charring. Adjust the solution to pH 7.4 \pm 0.1 at 5 °C with sodium hydroxide solution. Filler through cotton pad till clear filtrate is obtained. Fill into bacteriological tubes to 10 ml mark. Sterilize in an autoclave 121°C for 15 minutes.

C-4 PROCEDURE

- **C-4.1** Dilution Weigh 11 g of the material from the samples for bacteriological examination using a sterile spatula and suspend in 99 ml of dilution water at 45 °C. Agitate mildly, soak for one to three minutes and then agitate vigorously to avoid churming out the fat. Prepare dilutions of this and add on millilitre of suitable dilutions in triplicate to the sterile petri dishes.
- C-4.2 Pouring plates Melt the medium (see C-3.2.1) in bacteriological tubes and keep at 48 $^{\circ}$ C to 50 $^{\circ}$ C. Introduced this medium aseptically at 42 $^{\circ}$ C to 44 $^{\circ}$ C into the petri dishes and mix by rotating and tilting dishes without spreading over the edges, spread the mixture evenly over the bottom of the plate. Allow to solidify, after solidification of medium in plate, add cover layer of the medium.
- C-4.3 Incubation Invert plates and incubate at 35 °C to 37 °C for 24 hours.
- C-4.4 Counting Count the dark red colonies which have a diameter of 0.5 mm or over.
- C-4.5 Computation Compute the coliform count per gram from the dilutions used (see C-4.1).

NOTE 5: In case of doubt regarding the colonies developed on violet red bile agar representative colonies are picked and transferred to lactose bile salt broth in tubes having inverted vials. Production of acid and gas in confirmatory for coliform organisms.

NOTE 6: All precautions shall be observed to prevent microbiological contamination throughout the test.

Annex D Table -1, Item (ix) Alcohol test

D-1 Alcohol Test

The test is quick and simple. It is based on instability of the proteins when the levels of acid and/or rennet are increased and acted upon by the alcohol. Also increased levels of albumen (colostrum milk) and salt concentrates (mastitis) results in a positive test.

D-2 Procedure

The test is done by mixing equal amounts of milk and 68% of ethanol solution in a small bottle or test tube. 68 % Ethanol solution is prepared from 68 ml 96% (absolute) alcohol and 28 ml distilled water. If the tested milk is of good quality, there will be no coagulation, clotting or precipitation, but it is necessary to look for small lumps. The first clotting due to acid development can first be seen at 0.21 - 0.23 % Lactic acid. For routine testing 2 ml milk is mixed with 2 ml 68 % alcohol.

ORAFI FOR COMMENTANCE PURPOSE ON THE PROPERTY OF THE PROPERTY

Bangladesh Standard SPECIFICATION FOR PASTEURIZED LOW FAT MILK AND STANDARDIZED MILK (Draft for First Revision)

1. SCOPE

1.1 This standard prescribes the requirements and the method of sampling and tests for pasteurized low fat milk and standardized milk.

2. REFERENCES

2.1 The Bangladesh Standards listed in Annex A is necessary adjuncts to this standard. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

3. TERMINOLOGY

- 3.1 For the purpose of the specification the following definitions shall apply:
- **3.2 Milk** Milk is the normal lacteal secretion derived from complete milking of healthy animal without either addition of thereto or extraction therefrom. It shall be free from colostrum and obtained by the complete milking of one or more healthy animals (cow, buffalo, sheep or goat).
- 3.3 Whole milk/Full cream milk Whole milk/Full cream milk means any of the milk mentioned under section 3.2 or adding water¹ in Whole milk powder/Full cream milk powder which obtain through spray-drying process (comply with the requirements of BDS 860). In both cases, minimum milk fat and milk solids-not-fat content are 3.5 and 8.0 respectively.
- 3.4 Medium fat milk Medium fat milk which obtain from milk (see section 3.2) having milk fat minimum 2.0 % (m/m) and not more than 3.4 % (m/m).
- 3.5 Low fat milk Low fat milk which obtain from milk (see section 3.2) having milk fat minimum 0.5 % (m/m) and not more than 1.9 % (m/m).
- 3.6 Fat free/skimmed milk Fat free/skimmed milk which obtain from milk (see section 3.2) having milk fat less than 0.5 % (m/m).
- **3.7 Skimmed milk powder** A product obtained by the removal of water only from skimmed milk (see section **3.6**) of cow, buffalo, sheep or goat (section **3.2**) through spray-drying process and comply with the requirements of BDS 860.
- 3.8 Reconstituted milk Milk prepared by dispersing whole milk powder/full cream milk powder (comply with the requirements of BDS 860) in water¹ in the amount necessary to re-establish the appropriate water-to-solids ratio only to achieve similar characteristics and appropriate compositional requirements of medium fat milk or low fat milk or fat free/skimmed milk (see section 3.4, 3.5, and 3.6 respectively).

¹Water means drinking water, which obtain from a treatment process and conform BDS 1240

- 3.9 Standardized milk Standardized milk is the milk which fat and/or solids-not-fat (SNF) content have been adjusted to a certain pre-determined level. The standardization can be done by partially skimming of fat in the milk (see section 3.2) with a cream separator, or by admixture with fresh or reconstituted skimmed milk/reconstituted whole milk in proper proportions to adjust prescribed milk fat and SNF content. Fat content of standardize milk shall be minimum 1.9 % (m/m) but not more than 3.4 % (m/m).
- 3.10 Toned milk Milk obtained by adding water and skimmed milk powder (see section 3.5) to whole milk. Fat content of toned milk shall be more than 2.0 % (m/m) but less than 3.5 % (m/m).
- 3.11 Pasteurized medium fat milk Pasteurized medium fat milk is the milk obtain through pasteurization (see section 4) of medium fat milk (see section 3.4) and fulfilled the requirements described in section 5 of this standard.
- 3.12 Pasteurized low fat milk Pasteurized low fat milk is the milk obtain through pasteurization (see section 4) of low fat milk (see section 3.5) and fulfilled the requirements described in section 5 of this standard.
- 3.13 Pasteurized fat free/skimmed milk Pasteurized fat free/skimmed milk is the milk obtain through pasteurization (see section 4) of fat free/skimmed milk (see section 3.6) and fulfilled the requirements described in section 5 of this standard.
- 3.14 Pasteurized Reconstituted milk Pasteurized reconstituted milk is the milk obtain through pasteurization (see section 4) of reconstituted milk (see section 3.8) and fulfilled the requirements described in section 5 of this standard.
- 3.15 Pasteurized standardized milk Pasteurized standardized milk is the milk obtain through pasteurization (see section 4) of Standardize milk (see section 3.9) and fulfilled the requirements described in section 5 of this standard.
- 3.16 Pasteurized Toned milk Pasteurized toned milk is the milk obtain through pasteurization (see section 4) of toned milk (see section 3.10) and fulfilled the requirements described in section 5 of this standard.
- 4 Pasteurization It shall refer to:
 - a) the process of heating every particle of milk at a specified temperature;
 - holding the milk at such temperature continuously for a specified period in standard and properly operate of equipment, and
 - c) immediate cooling in the same equipment after heating.
- **4.1 Holding or Batch method** Milk is heated to at least 65 °C and held continuously at that temperature for at least 30 minutes and then immediately cooled in the same equipment to 4.4 °C or less to prevent the growth of the souring organism (largely proteolytic spore formers).
- **4.2 High Temperature Short Time (HTST) Method** In this method milk is heated at least 75 °C and held continuously at that temperature for at least 16 seconds and then immediately cooled in this equipment to 4.4 °C or less.
- **4.3** Flash pasteurization The temperature of milk shall be raised to not less than 80 °C and retained at this temperature for at least 10 s and immediately and rapidly cooled to 10 °C or less. Water means drinking water, which obtain from a treatment process and conform BDS 1240

5. REQUIREMENTS

Physical, chemical and microbiological requirements of milk described in section 3.11 to 3.16 are as follows:

- **5.1 Description –** Milk (see section **3.11** to **3.16**) shall have white yellowish opaque colour with fresh sweetish characteristic flavour of liquid milk. It shall be free from visible dirt and extraneous matter. It shall not contain whey powder, preservatives, detergent, or any other added substances except water¹ only for pasteurized reconstituted milk.
- **5.1.1** All products shall be free from any kind of foreign fat (other than milk fat) and solids. Milk fat in any form like, cream, butter, butter oil, ghee etc. are not allowed to add in milk for standardization and reconstitution purpose.
- **5.2 Hygienic condition –** The material shall be prepared in the premises maintained in accordance with BDS 822.
- **5.3 Legal requirement –** The product shall also comply in all other aspects with the requirements of the legislations enforced in the country.
- 5.4 The material shall also comply with the requirements given in Table 1

TABLE 1: REQUIREMENT FOR PASTEURIZED LOW FAT MILK AND STANDARDIZED MILK (Clause 3.11 – 3.16)

SI No.	Characteristic	Requirement	Method of Test
(1)	(2)	(3)	(4)
(i)	Milk Fat, %, (m/m), a) pasteurized medium fat milk	>2.0 - ≤3.4	ISO 2446
	b) pasteurized low fat milk	>0.5 - < 2.0	
	c) pasteurized fat free/skimmed milk	Max. 0.5	
	d) pasteurized standardized milk	1.9 - 3.4	
	e) pasteurized reconstituted milk:		
	(e-i) pasteurized reconstituted medium fat milk	(e-i) >2.0 - ≤3.4	
	(e-ii) pasteurized reconstituted low fat milk	(e-ii) >0.5 - < 2.0	
	(e-iii) pasteurized reconstituted fat free/skimmed milk	(e-iii) Max. 0.5	
	f) pasteurized toned milk	>2.0 - <3.5	
(ii)	Solids-not-fat (SNF), percent by mass, Min.	8.0	ISO 6731
		9.0*	
(iii)	Density, g/ml at 15.5 °C	1.028-1.036	See NOTE- 1
(iv)	Lactose, percent by mass, Min.	4.4	ISO 5548
(v)	Protein, percent by mass, Min.	3.0	ISO 8968-1
(vi)	Titratable acidity (as Lactic acid per 100 ml of milk), Max.	0.18	ISO TS 22113:2012
(vii)	Total plate count, CFU per ml, Max.	30,000	ISO 4833-1
(viii)	Total coliform count, CFU per ml. Less than	10	Annex B
(ix)	Phosphatase test	Negative	Annex C
(x)	Alcohol test	Negative	Annex D

^{*} Solids-not-fat (SNF), percent by mass, Min. subject to pasteurized toned milk only

NOTE -1: Density of normal milk may be determined by hydrometer (lacto-meter)

¹Water means drinking water, which obtain from a treatment process and conform BDS 1240

- Pesticides and veterinary drug residues, heavy metal and Aflatoxin M_1 5.5
- The product may comply with the requirements described in Bangladesh Food Safety Authority's 5.5.1 Regulation. This characteristic shall be tested only if considered as necessary.

Packing and Marking 6.

- Packing Pasteurized low fat milk and standardized milk mentioned in (see section 3.11 to 3.16) 6.1 shall be filled in clean, sound and sanitary containers made of glass or food grade polyethylene pouches, inner laminated tetra pack, plastic containers, cans or any other suitable materials or dispensing units. The product when marketed shall be packaged in well-sealed containers in order to prevent spoilage or contamination of the product. The packaging material used shall be food grade light proof, gas proof, mechanically strong, non-toxic and do not impart any off-flavour to the milk.
- All packets/containers shall be clean and free from chips, cracks and any other defects. Bottles shall be hermetically sealed with new and clean closures and cans shall be sealed with new and clean can closures. The plastic container shall be heat sealed along one or more edges and shall not leak after it is filled with the products. All containers shall be subjected to cleansing and sanitizing process before filling.
- Labeling All labelling information shall be in Bangla and if necessary, any other suitable 6.2 languages. The following information shall appear legibly on each container or label. Labels shall be clear in readable form of normal vision, easily visible and pasted securely. Brand name and product name shall be close together in front panel preferably in similar font size. Product name shall not smaller than two font size of the brand name.
 - a) Name of the product: 'Pasteurized medium fat milk/Pasteurized low fat milk/Pasteurized fat free or skimmed milk/Pasteurized standardized milk/Pasteurized toned milk/Pasteurized reconstituted (medium fat/low fat/fat free or skimmed) milk' as applicable;

- (i) For Pasteurized medium fat milk/Pasteurized medium low fat milk/Pasteurized fat free or skimmed milk declaration on label shall be "Prepared from fresh milk".
- (ii) For pasteurized standardized milk and pasteurized toned milk declaration on label shall be "Prepared by adding skimmed milk with fresh milk/Reconstituted skimmed milk with fresh milk/ Reconstituted milk with fresh milk'.
- (iii) For pasteurized reconstituted milk declaration on label shall be "Prepared by mixing water with milk Powder"
- b) Fat ----- percent [See item (i) of Table 1];
- c) Batch or code number;
- d) Name and address of the manufacturer/importer;
- e) Net volume of the contents in litres or milliliters;
- f) Nutritional information;
- f) Date of packing;
- g) Date of expiry;
- h) Storage and user instruction;
- i) Maximum Retail Price (MRP) and
- j) Any other requirements as specified in the current Legislations and Regulation enforced in the
- 6.2.1 The container or label shall be marked with the BSTI Certification Mark

NOTE: The use or BSTI Certification Mark is governed by the provisions of the Bangladesh Standards and Testing Institution Act, 2018 and the Rules and Regulations made there under. Details of conditions under which a licence for the use of BSTI Certification Mark may be granted to manufacturers or processors or importer may be obtained from the Bangladesh Standards and Testing Institution.

7. SAMPLING

7.1 The method of drawing representative samples of the material and the criteria for conformity shall be as prescribed in BDS 1009.

8. TESTS

- 8.1.1 Tests shall be carried out as prescribed by the methods specified in column 4 of Table 1.
- 8.2 Quality of regents Unless specified otherwise, pure chemicals shall be employed in tests and distilled water (see BDS 833) shall be used where the use of water as a reagent is intended.

NOTE 3: 'Pure chemicals' shall mean chemicals that do not contain impurities, which affect the result of analysis.

Annex A (Clause 2) List of Relevant Standards

BDS and ISO No.	Title	
BDS 103	Methods of rounding off numerical value	
BDS 822	Code of hygienic conditions for food processing units	
BDS 833	Water for laboratory use	
BDS 1009	Method of sampling and test for milk and milk products	
BDS 1240	Drinking water	
ISO 2446:2008	Milk - Determination of milk fat content	
ISO 4833-1:2013	Microbiology of the food chain — Horizontal method for the enumeration of microorganisms — Part 1: Colony count at 30 degrees C by the pour plate technique	
ISO 5548:2004	Caseins and caseinates - Determination of lactose content - Photometric method	
ISO 6731:2010	Milk, cream and evaporated milk – Determination of total solids content (Reference method)	
ISO 8968-1	Milk and milk products - Determination of nitrogen content - Part 1: Kjeldahl principle and crude protein calculation	
ISO TS 22113:2012	Milk and milk products — Determination of the titratable acidity of milk fat	

ANNEX B [Table 1, item (viii)] DETERMINATION OF COLIFORM COUNT

B-1 GENERAL

B-1.1 Coliform Bacteria – Coliform bacteria include all aerobic and facultative anaerobic gram negative non-spore forming bacteria which ferment lactose with the production of acid and gas. A positive presumptive test is indicated by formation of acid and gas within 48 hours at 35 °C to 37 °C in a fermentation tube containing lactose bile salt broth. Alternatively, the development of dark red colonies at least 0.5 mm in diameter in a solid medium (violet red bile agar) within 20 to 24 hours at 35 °C to 37 °C may be considered as a positive evidence of the presence of coliform bacteria. Violet red bile agar is one of the standard media used for determination of general types of coliform organisms including those of faecal origin in water, milk and other materials or sanitary importance.

B-2 APPARTUS

- B-2.1 Weighing scoop sterile with counter mass (weight)
- B-2.2 Bacteriological transfer pipettes sterile accurately graduated, with cotton plug in the upper orifice.
- **B-2.3** Dilution bottles, sterile made of heat-resistance glass (preferably silicate glass) closed with rubber stoppers (preferably screw cap) with new friction-fit liners for making them leak-proff and of the following capacities:
 - a) 150 ml with mark at 99 ml level; and
 - b) 25 ml with mark at 9 ml level.
- **B-2.4** Petri dishes with outside dish diameter 100 mm, inside dish diameter 91 mm and depth 15 mm. The exterior and interior surfaces of the bottom should be flat and free from bubbles scratches or other defects which would interfere with counting of colonies.
- B-2.5 Bacteriological tubes sterile 25 ml capacity with a mark at the 10 ml level, with cotton plugs.
- B-2.6 Tubes having inverted vials Durham tubes.

B-3 REAGENT

- **B-3.1** Dilution water Dissolve 34 g of potassium dihydrogen phoshate (KH₂PO₄) in 500 ml of distilled water, adjust with 1 N sodium hydroxide solution and make up to one litre with distilled water. Dilute 1.25 ml of this stock phoshpate buffer solution with distilled water to one litre to obtain dilution water.
- B-3.2 Medium Violet red bile agar of following composition and pH shall be used as the medium:

Yeast extract	3.0 g
Peptone	7.0 g
Sodium taurocholate	1.5 g
Lactose	10.0 g
Sodium chloride	5.0 g
Agar-agar	20.0 g
Indicator	
Neutral red	0.03 g
Crystal violet	0.002 g
Water	100 ml
Final pH	7.4 ± 0.1

B-3.2.1 Preparation and sterilization of medium - Soak the materials (B-3.20) for 3 to 5 minutes in cold water, then bring the mixture into complete solution with minimum delay by boiling above asbestos centered wire gauze, over a flame. Stir continuously and efficiently to avoid charring. Adjust the solution to pH 7.4 ± 0.1 at 5 °C with sodium hydroxide solution. Filler through cotton pad till clear filtrate is obtained. Fill into bacteriological tubes to 10 ml mark. Sterilize in an autoclave 121 °C for 15 minutes.

B-4 PROCEDURE

B-4.1 Dilution - Weigh 11 g of the material from the samples for bacteriological examination using a sterile spatula and suspend in 99 ml of dilution water at 45 °C. Agitate mildly, soak for one to three minutes and then agitate vigorously to avoid churming out the fat. Prepare dilutions of this and add on millilitre of suitable dilutions in triplicate to the sterile petri dishes.

- **B-4.2** Pouring plates Melt the medium (see B-3.2.1) in bacteriological tubes and keep at 48 $^{\circ}$ C to 50 $^{\circ}$ C. Introduced this medium aseptically at 42 $^{\circ}$ C to 44 $^{\circ}$ C into the petri dishes and mix by rotating and tilting dishes without spreading over the edges, spread the mixture evenly over the bottom of the plate. Allow to solidify, after solidification of medium in plate, add cover layer of the medium.
- B-4.3 Incubation Invert plates and incubate at 35 °C to 37 °C for 24 hours.
- B-4.4 Counting Count the dark red colonies which have a diameter of 0.5 mm or over.
- B-4.5 Computation Compute the coliform count per gram from the dilutions used (see B-4.1).
- NOTE 4: In case of doubt regarding the colonies developed on violet red bile agar representative colonies are picked and transferred to lactose bile salt broth in tubes having inverted vials. Production of acid and gas in confirmatory for coliform organisms.
- NOTE 5: All precautions shall be observed to prevent microbiological contamination throughout the test.

Annex C [Table 1, Item (ix)] Phosphatase Test

- **C-1** Alkaline phosphatase is an indigenous milk enzyme. The enzyme activity is destroyed at pasteurization temperature and has been adopted as an index of the efficiency of pasteurization. Since milk is a proven vector for a number of pathogenic bacteria, including *Salmonella*, *Campylobactor* and *Listeria*, the test is very great significance to the dairy industry as a means of policing the thoroughness of heat treatments or the addition of raw milk to heated or unheated products. In the following method, a solution of disodium p-nitrophenyl phosphate in a buffer of pH 10.2 is used as substrate. The compound, colourless in solution, is hydrolyzed by alkaline phosphatase of milk to liberate *p*-nitrophenol, which under alkaline condition gives an intense yellow colouration to the solution. The liberated *p*-nitrophenol is measured by direct comparison with standard colour discs in a Lovibond comparator. The test does not apply to sour milk and milk preserved with chemical preservatives.
- C-2 Reagents/Apparatus All reagents should be of analytical grade.
- **C-2.1** Buffer solution 1.5 g of sodium bicarbonate and 3.5 g of anhydrous sodium carbonate dissolved in water and made up to one litre. Store in a refrigerator and discard after 1 month.
- C-2.2 Disdium p-nitrophenylphosphate The solid substrate must be kept in the refrigerator.
- C-2.3 Buffer-substrate solution Weigh accurately 0.15 g of subtrate (disodium p-nitrophenyl phosphate) into a 100 ml measuring cylinder and make up to 100 ml with buffer solution. The solution should be stored in refrigerator and protected from light. The solution should give a reading of less than the standards marked 10 on comparator disc APTW or APTW 7 when viewed through a 25 mm cell (distilled water is used as blank). The solution must be discarded after one week.
- C-2.4 A lovibond comparator with stand for work in reflected light.
- C-2.5 A lovibond comparator disc APTW or APTW 7.
- C-2.6 Two fused glass cells of 25 mm depth.
- C-2.7 A water bath or incubator capable of being maintained at 37.5 °C ± 0.5 °C.
- C-2.8 One ml pipette and 5 ml pipette.
- C-2.9 One litre graduated flask.

- C-2.10 100 ml measuring cylinder.
- C-2.11 Test tubes, nominal size 150/16 mm with rubber stoppers.
- C-3 Procedure Into a test tube pipette 5 ml of buffer substrate solution, stopper and bring the temperature to 37 °C. Add 1 ml of test milk to it shake and replace stopper, incubate at 37 °C for 2 hours. Incubate one blank prepared from boiled milk of the same type as that undergoing the test with each series of sample. Remove the tubes after 2 hours and the content should be well mixed. Place the boiled milk blank on left hand side of the comparator stand and test sample on the right. Take reading in reflected light by revolving the disc until the test sample is matched. Record readings failing between two standards by affixing a plus or minus sign to the figure for the nearest standard.
- C-4 Interpretation The test is considered satisfactory if it gives a reading of 10 μg or less of p-nitrophenyl per ml of milk. Properly pasteurized milk gives no discernible colour.

Precautions Note 6: All glassware must be cleaned before use. Cleaning should be done by soaking in Chromic acid solution prepared by slowly adding 4 volumes of concentrated H₂SO₄ to 5 volumes of 8 % potassium dichromate. After cleaning in chromic acid glassware must be rinsed in warm water and distilled water and finally dried. Glassware used for the test must not be used for any other purpose and must be kept apart from other apparatus in the laboratory.

Precautions Note 7: A fresh pipette must be used for each sample of milk. Pipettes must not be contaminated with saliva.

Precautions Note 8: The sample of milk should be examined as soon as possible after arrival at the laboratory. If not examined immediately it must be kept at a temperature between 3 °C and 5 °C until examined. The sample must be brought to room temperature immediately before being tested.

Annex D
Table -1, Item (x)
Alcohol test

D-1 Alcohol Test

The test is quick and simple. It is based on instability of the proteins when the levels of acid and/or rennet are increased and acted upon by the alcohol. Also increased levels of albumen (colostrum milk) and salt concentrates (mastitis) results in a positive test.

D-2 Procedure

The test is done by mixing equal amounts of milk and 68 % of ethanol solution in a small bottle or test tube. 68 % Ethanol solution is prepared from 68 ml 96 % (absolute) alcohol and 28 ml distilled water. If the tested milk is of good quality, there will be no coagulation, clotting or precipitation, but it is necessary to look for small lumps. The first clotting due to acid development can first be seen at 0.21 - 0.23 % Lactic acid. For routine testing 2 ml milk is mixed with 2 ml 68 % alcohol.