



Bangladesh Standards and Testing Institution
Member: ISO, OIML, APMP, Alimentarius Commission of FAO/WHO
Ministry of Industries
Government of the People's Republic of Bangladesh



Ref: 36.05.014.23.00.056.2018

Dated: 16.10.2019

Deputy Commissioner of Customs
Custom House,
Chattogram sea port
Chattogram.

Subject: NOC for release of Water Bath H.S Code No. 6910.90.00

Dear Sir,

I would like to request you that under the 'Establishment & Modernization of BSTI Regional Offices at Chattogram & Khulna(1st Revised)' Project L/C no. 036919010011, Dated: 30.01.2019 item of water bath like as H.S code No. 6910.90.00 is not mandatory item of BSTI Certification Marks (CM) license. It is noted that water bath is a device used in the laboratories to incubate samples in water maintained at a constant temperature. It is made of stainless steel products not ceramics products. I attached the technical Specification herewith for your kind information.

So, you can arrange the necessary action for release the above mentioned water bath H.S code No. 6910.90.00.

Thank you for your co-operation.

(Mohammad Abu Tarek)
Deputy Director (Food & Bact.) &
Project Director,
(Chittagong & Khulna Project), BSTI,
Dhaka.
Mobile: 01715005173

	<p>Temperature deviation over time at 37 °C: ± 0.2 °C or better Footprint m2 / sqft :0.3 / 3.2 or equivalent Chamber volume L :56L Min or more Dimensions chamber, mm / in (W x H x D) Approx: 354 x 508 x 414 / 13.9 x 20.0 x 16.3 or equivalent, Exterior, mm / in (W x H x D) Approx: 530 x 755 x 565 / 20.9 x 29.7 x 22.2 or equivalent Number of shelves supplied / positions 2 / 13 Max. shelf load kg: 25 or more Rated voltage / frequency V / Hz 120 / 60 Rated power / max. current W / A 300 / 2.5 Weight Approx: kg 40 Energy consumption at 37 °C:W 21 Calibration certificate supplied by bidder from Manufacturing Country accredited lab. Standard: USA/UK/Germany/Japan or EU</p>			
14.	<p>Centrifuge Machine Microprocessor controlled bench top centrifuge Speed, rpm : 5000 or more Fixed angle rotor Capacity : 6 x 50 mL or more Timer Range :10 second to 99h 59min, continuous Standards & Certifications: IEC 61010-1, IEC 61010-2-020, IEC 61010-2-101, EN 61326-1, UL Listed, CE marked, IVD compliant, Certified biocontainment1 Power:230VAC, 50Hz. Calibration certificate supplied by bidder from Manufacturing Country accredited lab. Standard: USA/UK/Germany/Japan or EU</p>	Germany	<p>Make: HermleLabortechnik GmbH, Germany Model: Z366-E</p>	02
15.	<p>Hotplate digital ceramic top Size: 280x280mm, Temp.: 350°C min, Power:230VAC, 50Hz. Calibration certificate supplied by bidder from Manufacturing Country accredited lab. Standard: USA/UK/Germany/Japan or EU</p>	Germany	<p>Make: Heidolph Instruments GmbH & Co. KG, GERMANY Model:MR Hei-Tec</p>	02
16.	<p>Water Bath Water bath complete with a removable stainless steel perforated shelf with universal flask tray. Outer & inner : Stainless steel or better Display : Digital Control & Display of Temperature and time, Control Feature : Illuminated on/off switch and heater on indicator, Capacity : 20L or more, Temperature range : Ambient +5 to 99.9°C or higher range Standard: USA/UK/Germany/Japan or EU</p>	USA	<p>Make: Poly Science, USA. Model:WB20A11B</p>	02
17.	<p>Trinocular Microscope Eyepiece : Siedentopf type Trinocular Head, Inclined at 30°, 360° Rotatable, Objective : WF10x/20x Plan achromatic objective 4x(N.A0.10, W.D15.5mm), 10x(N.A0.25, W.D5.02mm), 40x(N.A0.65,W.D0.60mm), 100x(N.A1.25, W.D0.13mm) or equivalent Nosepiece : Backward quadruple nosepiece or better Stage : Rectangular 216x150mm, cross travel 78x54mm, using low-positioned, Condenser: 1.25 N.A Abe condenser with iris diaphragm, Illumination: 6V/20W variable quartz halogen light source or equivalent Complete with photographic system. Optical system: UIS2 optical system (infinity-corrected) Microscope frame Illumination Reflected/transmitted External 12 V 100 W light source Light preset switch LED voltage indicator Reflected/transmitted changeover switch Focus Motorized focusing</p>	Japan	<p>Make: MEIJI TECHNO CO, Ltd, Japan. Model: MT6300</p>	01